

Industrial Grounding & Bonding Verification: Effective Ground-Fault Current Path in Raceways and Cable Tray

A field checklist to prove the fault-clearing path is continuous and low-impedance

A circuit breaker can only clear a ground fault if the fault current has a continuous, low-impedance path back to the source. When bonding jumpers are missing across cable tray expansion joints, loose splice bolts choke that current below the breaker's trip threshold — and the fault burns instead of clearing. This checklist captures the verification steps that prevent the failure mode behind a documented 480V cable tray ground-fault fire.

Use it at commissioning, after any raceway modification, and as part of periodic maintenance. Sign each line. File the completed checklist with the commissioning or work-order package.

COMPANION RCA

The Broken Path: Cable Tray
Ground Fault Fire

AUDIENCE

E&I crews, contractors,
commissioning / QA, maintenance
planners

STANDARDS

NEC 250 & 392, IEEE 142, CEC
Section 10, NETA MTS

Use this checklist to verify the effective ground-fault current path wherever a metallic raceway or cable tray serves as, or carries, the equipment grounding conductor. Each item must be verified and signed off. Metal touching metal is not a ground path — if you cannot measure it, do not assume it.

1. CABLE TRAY & RACEWAY BONDING

☐ **Listed bonding jumpers installed across all expansion joints.**

Every expansion / discontinuity joint bridged with a listed flexible bonding jumper. Splice plates and bolts are mechanical hardware, not the fault path.

☐ **Bonding restored across every cut or modified section.**

Each section that was cut, added, or re-routed has its bonding re-established and re-tested as part of the modification.

☐ **Bonding jumpers sized correctly.**

Jumpers sized for the largest upstream overcurrent device per NEC 250.122.

PASS CRITERIA – JOINT BONDING

Do not rely on splice-plate bolts for continuity. Each bonded joint should read essentially negligible resistance — typically $< 0.1 \Omega$ across a single connection — measured with a low-resistance (DLRO) ohmmeter.

2. EQUIPMENT BONDING

☐ **Paint removed at all lug landings.**

Coatings removed where ground lugs land on enclosures and tray to guarantee metal-to-metal contact, per NEC 250.96.

☐ **Listed lugs and connectors, torqued to spec.**

Grounding/bonding connectors listed for the conductor and surface, installed and torqued to the manufacturer's value.

☐ **Isolated and separately derived grounds bonded back to service.**

Any isolated ground or separately derived system correctly bonded to the main service grounding system — no floating grounds.

3. DEDICATED EQUIPMENT GROUNDING CONDUCTOR

☐ **Sized green EGC pulled in the tray.**

A dedicated, sized equipment grounding conductor run in the tray alongside the power cables so continuity does not depend on tray joints alone.

☐ **EGC bonded to each tray section and load.**

The dedicated EGC bonded to every tray section and to each connected piece of equipment to provide a redundant fault path.

4. CONTINUITY & RESISTANCE TESTING

☐ **Point-to-point resistance test performed.**

Resistance measured from the farthest point of the raceway back to the main service ground bus with a low-resistance ohmmeter.

☐ **Tested at commissioning and periodically.**

Ground-path continuity verified before energization and re-verified on a periodic basis over the life of the installation.

☐ **Path proven low enough to operate upstream protection.**

Confirmed that prospective ground-fault current over the measured path exceeds the upstream device's trip threshold so the fault clears fast.

PASS CRITERIA – EFFECTIVE GROUND-FAULT PATH

Per NEC 250.4(A)(5), the path must be electrically continuous, low-impedance, and capable of carrying the maximum imposed fault current. The measured end-to-end resistance must be low enough that the prospective fault current exceeds the breaker's instantaneous pickup. Record the value and the calculated fault current on the test sheet.

5. FAULT-CLEARING VERIFICATION

☐ **Available fault current vs. path impedance confirmed.**

The arc-fault and bolted-fault current at the load end verified against the protective device's clearing characteristic.

☐ **Ground-fault protection applied where faults can sit below pickup.**

Where arcing ground faults can remain below the overcurrent pickup, GFPE / ground-fault relaying is applied so low-level faults still clear.

REFERENCE STANDARDS

- **NEC 250.4(A)(5)** — Effective ground-fault current path — continuous, low-impedance, fault-rated
- **NEC 250.96 / 250.122** — Bonding for continuity; sizing of equipment grounding/bonding conductors
- **NEC 392.60** — Cable tray as equipment grounding conductor; bonding jumper requirements
- **IEEE 142 (Green Book)** — Grounding of industrial and commercial power systems
- **CEC Section 10** — Grounding and bonding (Canadian Electrical Code)
- **NETA MTS** — Maintenance Testing Specifications — ground/bonding resistance testing

DISCLAIMER & LIMITATION OF LIABILITY

This checklist is provided for educational and informational purposes only. It is a general industry reference, not a site-specific procedure, engineering specification, or legal compliance document. It does not replace the judgement of a qualified person, professional engineer, or authority having jurisdiction (AHJ).

Codes, standards, and regulations are revised periodically and vary by jurisdiction. **Verify the current edition of all referenced codes (CEC, NEC, CSA, NFPA, API, OSHA) and any provincial, state, or local amendments that apply to your work site before relying on the items listed here.** Where any conflict exists between this checklist and the applicable code, regulation, or your employer's safe work procedure, the code, regulation, or procedure governs.

ELI Intelligence and the authors of this material disclaim all liability for any loss, injury, or damage arising from the use of, or reliance on, this checklist. Use at your own risk and only under the supervision of competent persons trained for the work being performed.

GET THE FULL RCA AND THE NEXT CHECKLIST

This checklist accompanies the full incident analysis at safetyblog.eli-intelligence.com. New incident RCAs and field checklists publish every Friday. Subscribe at the site footer to get them in your inbox the morning they go live.